

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT) (51) International Patent Classification 6: WO 97/07664 (11) International Publication Number:

A01G 31/00 **A1** (43) Internati nal Publicati n Date: 6 March 1997 (06.03.97)

(21) International Application Number: PCT/EP96/03847

(22) International Filing Date:

30 August 1996 (30.08.96)

(30) Priority Data:

95202344.8 30 August 1995 (30.08.95) EP (34) Countries for which the regional or international application was filed: AT et al. 95203375.1 7 December 1995 (07.12.95) EP (34) Countries for which the regional or international application was filed:

AT et al.

(71) Applicant (for all designated States except US): ROCKWOOL INTERNATIONAL A/S [DK/DK]; Hovedgaden 584, DK-2640 Hedehusene (DK).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): DE GROOT, Jacob, Frank [NL/NL]; Elmpterweg 14, NL-6042 KK Roermond (NL). HUSEMOEN, Thor, Brede [NO/DK]; Rørholm 34, DK-4000 Roskilde (DK).
- (74) Agent: PRINS, Hendrik, Willem; Amold & Siedsma, Sweelinckplein 1, NL-2517 GK Den Haag (NL).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: HYDROPHILIC PLANT GROWTH SUBSTRATE COMPRISING A FURAN RESIN

(57) Abstract

The invention relates to a plant growth substrate, comprising a coherent, hydrophilic matrix of mineral wool fibres mutually connected via binder based on furan resin, and to use of a coherent, hydrophilic matrix of mineral wool fibres mutually connected via binder based on furan resin, as a plant growth substrate.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| AM | Armenia | GB | United Kingdom | MW | Malawi |
|----|--------------------------|----|------------------------------|----|--------------------------|
| ΑT | Austria | GE | Georgia | MX | Mexico |
| ΑU | Australia | GN | Guinea | NE | Niger |
| BB | Barbados | GR | Greece | NL | Netherlands |
| BE | Belgium | HU | Hungary | NO | Norway |
| BF | Burkina Faso | 1E | Ireland | NZ | New Zealand |
| BG | Bulgaria | IT | Italy | PL | Poland |
| BJ | Benin | JP | Japan | РT | Portugal |
| BR | Brazil | KE | Kenya | RO | Romania |
| BY | Belarus | KG | Kyrgystan | RU | Russian Federation |
| CA | Canada | KP | Democratic People's Republic | SD | Sudan |
| CF | Central African Republic | | of Korea | SE | Sweden |
| CG | Congo | KR | Republic of Korea | SG | Singapore |
| СН | Switzerland | KZ | Kazakhstan | SI | Slovenia |
| CI | Côte d'Ivoire | LI | Liechtenstein | SK | Slovakia |
| CM | Cameroon | LK | Sri Lanka | SN | Senegal |
| CN | China | LR | Liberia | SZ | Swaziland |
| CS | Czechoslovakia | LT | Lithuania | TD | Chad |
| CZ | Czech Republic | LU | Luxembourg | TG | Togo |
| DE | Germany | LV | Latvia | TJ | Tajikistan |
| DK | Denmark | MC | Monaco | TT | Trinidad and Tobago |
| EE | Estonia | MD | Republic of Moldova | UA | Ukraine |
| ES | Spain | MG | Madagascar | UG | Uganda |
| FI | Finland | ML | Mali | US | United States of America |
| FR | France | MN | Mongolia | UZ | Uzbekistan |
| GA | Gabon | MR | Mauritania | VN | Viet Nam |

HYDROPHILIC PLANT GROWTH SUBSTRATE COMPRISING A FURAN RESIN

The present invention relates to a hydrophilic plant growth substrate, more in particular to a substrate based on a coherent matrix of mineral wool which is hydrophilic due to the use of a specific cured resin.

Plant growth substrates may have the form of plugs accommodated in a tray hole, of cubes having a foil around the standing side surfaces, or of plastic wrapped slabs.

The nowadays used plant growth substrates which are based on a coherent matrix of mineral wool use as a cured binder generally a phenol-formaldehyde resin. Due to the use of this type of binders, the matrix of mineral wool has to be provided with a so-called wetting agent in order to impart the substrate with hydrophilic

15 properties. That is, the matrix can adsorb in a relatively short time period up to saturation amounts of water.

Although this type of known plant growth substrates are abundantly used, there is a constant research to improve plant growth substrates, in particular the phytotoxicity of the chemicals used. This phytotoxicity may result for instance from the used wetting agent, or due to the binder.

Accordingly the present invention relates to
25 plant growth substrates comprising a coherent,
hydrophilic matrix of mineral wool fibres mutually
connected via binder based on furan resin, and to the use
of products produced by using a furan resin, for the
culture of plants.

The plant growth substrates according to the invention comprise a coherent matrix of mineral wool. As mineral wool may be used stone wool, glass wool and/or slag wool. These matrices are produced using conventional

production methods which only depend on the starting

For the plant substrates according to the invention use may be made of a coherent matrix of mineral wool. Coherency is obtained by curing the applied furan resin such that the mutual fibres are mechanically connected, which connections are substantially water resistant. However, it is noted that the plant growth substrate may consist of a so-called granulate having the form of mineral wool flakes comprising a number of fibres and having a size of 0.2-5 cm.

When the plant growth substrate according to the present invention is cured and formed into a coherent hydrophilic matrix, the (higher density) substrate may have a compression strength up to 50 kPa, such as a compression strength in the range of 10-45 Kpa.

Hydrophilic character means in the context of the present invention that water is absorbed to a substantial extent/amount which may be measured in the so-called sinking test in water to which is not added any surfactant or mechanical force is applied to the substrate. It is noted that without the use of a wetting agent the plant growth substrate of the invention has good plant growth (hydrophylic) properties.

The furan resins that are used in the present invention are based on the polymerization of at least a furan molecule having the general formula

30

25

In this general formula A and B are polymerizable groups.

Due to polymerization are formed dimer, oligomer and
polymer molecules in which the furan ringstructure is

separated at least to one other furan structure by the
group A and/or B. Furthermore, the furan ring may be less
unsaturated, that is may comprise only one or no carbon-

carbon double bond at the 2, 3 or 4-position in the ringstructure.

The polymerizable groups A and B may be selected from hydrogen, C1-C10 alkyl groups,

- 5 polysubstituted vinyl radicals, polysubstituted aromatic groups, ketones, anhydrides, polysubstituted furfuryl, hydroxyls, aldehydes, carboxylic acids, esters, amines, imines, alkynes, alkyl halides, aromatic halides, olefinic halides, ethers, thiols, sulfides, nitriles,
- 10 nitro groups, sulfones, sulfonic acids, and mixtures thereof.

Accordingly, the repeating groups in the product obtained by polymerization comprise furan, furfural, furfuryl alcohol,

- 5-hydroxymethyl-2-furancarboxyaldehyde,
 5-methyl-2-furancarboxyaldehyde, 2-vinyl furoate,
 5-methyl-2-vinylfuroate; 5-tertbutyl-2-vinyl furoate,
 2-furfurylmethacrylate, 2-furfuryl methylmethacrylate,
 2-vinyl furan, 5-methyl-2-vinyl furan,
- 20 2-(2-propylene)furan (or 2-methyl vinylidene furan),
 5-methyl-2-methyl vinylidenefuran;
 furfurylidene acetone, 5-methyl-2-furfurylidene, aceton,
 2-vinyl tetrahydrofuran, 2-furyl oxirane,
 5-methyl-2-furyloxirane, furfuryl vinyl ether,
- 25 5-methyl-furfuryl vinyl ether,
 vinyl 2-furyl ketone,
 bis-2,5-carboxyaldehyde furan,
 bis-2,5-hydroxymethyl furan,
 5-hydroxymethyl-2-ethyl furanacrylate,
- 30 2,5-furandicarboxylic acid,
 - 2,5-furan diacid dichloride,
 - 2,5-furan dicarboxylic acid dimethyl ester,
 - 2,5-furan methylamine,
 - 5-carboxy-2-furan amine,
- 5-methylester-2-furan amine,
 bis-(2,5-methylene isocyanate) furan,
 bis(2,5-isocyanate) furan,
 2-isocyanate furyl, and

2-methylene isocyanate furyl.

The furan resins may be used as a concentrate or in diluted form in a suitable solvent, such as water. The solid content in a furan resin composition when injected may be as from 1 wt%, generally less than 40 wt%, such as 2-30 wt%, like 5-20 wt%. A suitable furan resin binder is a Farez M (TM) type from QO-Chemicals. Due to the use of these furan resins the plant growth substrate has an excellent brownish colour. The density of the substrate is about 10-150 kg/m³, such as 40-120 kg/m³.

The furan resin may be formed by polymerization, such as polyaddition polymerization and condensation polymerization. These polymerizations are known in the art.

In order to reduce the viscosity of the polymerization preparation to be used a co-solvent may be used. Suitable co-solvents are organic mono-, di- and polyacids, such as levulinic acid and maleic acid. Co20 solvents may be used in an amount up to 15 wt%, such as 2-10 wt% or generally 4-8 wt%.

In order to cure a furan resin, the furan resin composition may comprise a catalyst. Examples are inorganic and organic acids, such as hydrochloric acid and maleic acid. Other catalyst examples are Friedel-Crafts catalysts, such as aluminum chloride. Other examples are salts of inorganic and organic acids such as ammonium sulphate, ammonium nitrate and urea salt of toluene sulfonic acid. Depending on the type of catalyst there may be used up to 20 wt%, generally in the range of 1-15 wt%, such as preferably 8-10 wt%.

In order to improve the cohesion for binding to the fibre surface or fibre material a coupling agent may be included. Examples of coupling agents are silanes or organotitanates and organozirconates. Examples of suitable silane coupling agents are N-Methyl-3-aminopropyl-trimethoxysilane and 3-aminopropyl-triethoxysilane.

Furthermore, surfactants and extenders may be used in the furan resin composition.

In order to avoid dust formation during plant substrate production and handling a mineral, hydrophobic oil may be added, but the formed substrate maintains its hydrophilic properties.

In stead of using only furan-like molecules in the polymerization reaction, copolymerizations may be used as well, in which other monomers are used, such as formaldehyde and phenol. By using these co-monomers the hydrophilic properties of the resin may be adapted in the desired sense. Formaldehyde and phenol may be used in more amounts up to 50%, generally in an amount of 1-45%, such as 2-30%, exemplified 5-10%. Accordingly, due to the use of those monomers the hydrophilic character may be adjusted in the desired sense. However, when including other monomers in the binder composition, formaldehyde is a preferred monomer.

When using formaldehyde as a co-monomer, it is preferred to include in the furan resin composition a formaldehyde scavenger, such as ammonia or urea. Dependant on the amount of formaldehyde used ammonia and/or urea may be present in amounts up to about 5 wt%, such as 0.1-3 wt%, in particular 0.5-2 wt%.

25 Preferred is a furan resin based on furfurylalcohol and comprising a minor amount of formaldehyde, catalysts, formaldehyde scavengers and coupling agent.

This furan resin composition is used and applied to stone wool fibres after their formation while airborne. Furan resin is applied in such an amount that the resin content of the plant growth substrate is about 1-10 wt%, such as 1.5-5wt% in particular 2-3.5 wt%.

It is noted that even if during the production of the plant growth substrate according to the invention 0.2-0.5% impregnating oil was used water absorption does not alter and was still up to about 100%. Hereafter Table 1 gives properties of the plant growth substrates

6

according to the patent invention based on a furan resin, in particular a furfurylalcohol resin.

Table 1

5

| | Density | 100 kg/m³ | 45 kg/m³ |
|----|---------------------------|-----------|----------|
| | Resin content | 3.1wt% | 2.9wt% |
| | Compression strength | 43 kPa | |
| 10 | Aged compression strength | 36 kPa | |
| | Delamination strength | 11.5 kPa | |
| | Swelling | 2.5% | |
| | Water absorption | 100 vol% | 100 vol% |
| | Tensile strength | | 15.5 kPa |
| 15 | • | | |

SUBSTITUTE SHEET (RULE 26)

The following examples show the suitability of the hydrophilic plant growth substrates according to the invention, which comprise the furan resin binder. It is emphasized that the furan resin binder based substrates according to the invention do not contain a wetting agent. To the contrary the conventional phenolic resin based substrates used for comparison purposes in the example do contain traditional wetting agents. These examples are given for the purpose of illustrating the invention and not intended to limit the scope of the invention thereto.

Example 1

The plant growth substrate was conventionally produced in a density of 45 and 100 kg/m³ and used for plant growth (furan resin content about 3 wt%). Cucumber plants were grown on these substrates and resulted in plants growing and yielding cucumbers similar to plants grown on plant growth substrates based on phenol
20 formaldehyde resin and a wetting agent.

Example 2

Similar growth substrates of the invention as used in example 1 (further comprising 0.5% impregnating oil) were used for growing garden-cress (common nutrient solution; EC=1, pH 6.7). In comparison to a standard growth substrate or granulate no growth differences have been noted up to after eight days. In a toxicity test no growth differences were observed after eight days.

30

Example 3

Standard size growth blocks of the invention with furan resin as binder were tested in propagation trials set up in a greenhouse. The growth blocks

35 contained 2 wt% furan resin and during its production no mineral oil was added. Because the hydrophilic properties of the growth blocks are essential, the sinking time of the blocks were measured during the production and

excellent sinking times of only 8-12 seconds were obtained. Tomatoes and cucumbers were tested and the results were compared with growth blocks made of the same mineral wool but with phenolic resin as binder.

For tomatoes, 13 days after sowing the tomato plants were planted in the growth blocks and the results were collected 23 days after sowing.

For cucumber, sowing took place after saturation and the results were collected 22 days after 10 sowing.

The plant growth results (fresh weight [g/plant]) are as follows. Tomato plants 136,2 g/plant; and 116,2 g/plant for furan resin and phenolic resin, respectively.

15 For cucumbers the growth blocks comprising furan resin provided 82,3 gram per plant and phenolic resin growth blocks provided 81,5 gram per plant.

Example 4

Full scale growth trials in slabs at growers with cucumber, tomato and sweet pepper gave results from propagation tests as shown in Table 2. The slabs contained 2-3.3 wt% binder and the result is given for the growth substrate with furar resin as % of growth substrate with phenolic resin.

Table 2

| | CUCUMBER | TOMATO | SWEET PEPPER | |
|--------------|---------------|---------------|--------------|--|
| Plant height | 15 days: 99% | 14 days: 110% | 20 days: 99% | |
| | 22 days: 100% | 20 days: 113% | 28 days:104% | |
| Fresh weight | 15 days: 105% | 14 days: 105% | 20 days:102% | |
| | 22 days: 101% | 20 days: 109% | 28 days: 97% | |

Example 5

Full scale growth trials at growers with cucumber, tomato and sweet pepper gave the following conclusions evaluated after 4 to 6 months after planting date. No significant difference of furan resin bonded slabs compared with phenolic resin bonded slabs for penetration resistance, pH, water content and electrical conductivity. The furan resin bonded material has better rooting from the start, a slightly earlier forming of crop fruits and better slab strength.

CLAIMS

- 1. Plant growth substrate, comprising a coherent, hydrophilic matrix of mineral wool fibres mutually connected via binder based on furan resin.
- 2. Substrate as claimed in claim 1, wherein the 5 furan resin is obtained by polymerization of at least a furan molecule having the general formula

10

and/or its less unsaturated analogues, wherein A and B are each a polymerizable group.

- 3. Substrate as claimed in claim 2, wherein A and B are independently selected from the group comprising hydrogen, C1-C10 alkyl groups, polysubstituted vinyl radicals, polysubstituted aromatic groups, ketones, anhydrides, polysubstituted furfuryl, hydroxyls, aldehydes, carboxylic acids, esters, amines, imines, alkynes, alkyl halides, aromatic halides, olefinic halides, ethers, thiols, sulfides, nitriles, nitro groups, sulfones, sulfonic acids, and mixtures thereof.
 - 4. Substrate according to claim 2-4, wherein the furan molecule is furfurylalcohol.
- 5. Substrate as claimed in claim 1-4, wherein the 25 furan resin comprises a co-solvent.
 - 6. Substrate according to claim 1-5, wherein the furan resin comprises a polymerization catalyst.
 - 7. Substrate according to claim 1-6, wherein the furan resin comprises a coupling agent.
- 8. Substrate according to claim 1-7, wherein the furan resin comprises a surfactant, coloring agent and/or extender.

- 9. Substrate according to claim 1-8, wherein the furan resin is obtained by copolymerization.
- 10. Substrate according to claim 1-9, wherein the polymerization comprises further formaldehyde and/or phenol.
 - 11. Substrate according to claim 10, wherein the furan resin comprises a formaldehyde scavenger.
 - 12. Substrate according to claim 1-11, having a density of 15-150 kg/m³.
- 13. Substrate according to claim 1-12, wherein the binder is cured.
 - 14. Use of a coherent, hydrophilic matrix of mineral wool fibres mutually connected via binder based on furan resin, as a plant growth substrate.
- 15 15. Use according to claim 14, wherein the binder is cured.

| 6 | If | itional | Application | No |
|---|----|---------|-------------|----|
| | PC | T/EP | 96/038 | 47 |

| A. CLASSI | FICATION OF SUBJECT MATTER A01G31/00 | | | | | |
|---|---|--|-----------------------|--|--|--|
| | | | | | | |
| | o International Patent Classification (IPC) or to both national classification | lication and IPC | | | | |
| | SEARCHED ocumentation searched (classification system followed by classification) | ion cymbols) | | | | |
| IPC 6 | A01G | on symbols, | | | | |
| | | | | | | |
| Documentat | on searched other than minimum documentation to the extent that | such documents are included in the fields se | arched | | | |
| | | | | | | |
| Electronic d | ata base consulted during the international search (name of data bas | e and, where practical, search terms used) | | | | |
| | | • | | | | |
| | | | | | | |
| C DOCUM | EENTS CONSIDERED TO BE RELEVANT | | | | | |
| Category * | Citation of document, with indication, where appropriate, of the re | elevant passages | Relevant to claim No. | | | |
| | | | TOTOLIN W CIMIN 110. | | | |
| A | DE,A,40 24 727 (GRÜNZWEIG) 6 Febr see claims 1,5 | ruary 1992 | | | | |
| A | US,A,3 854 988 (ASHALL) 17 Decemb see the whole document | per 1974 | 1 | | | |
| A | FR,A,2 291 251 (WILMSEN) 11 June see page 2, line 25 - line 27; cl | | 1 | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | L | | | | | |
| Further documents are listed in the continuation of box C. Patent family members are listed in annex. | | | | | | |
| * Special categories of cited documents : "T" later document published after the international filing date | | | | | | |
| | "A" document defining the general state of the art which is not considered to be of particular relevance on priority date and not in conflict with the application but cited to understand the principle or theory underlying the | | | | | |
| "E" earlier document but published on or after the international "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to | | | | | | |
| *L* document which may throw doubts on priority claim(s) or involve an inventive step when the document is taken alone which is cited to establish the publication date of another 'Y' document of particular relevance; the claimed invention | | | | | | |
| citation or other special reason (as specified) cannot be considered to involve an inventive step when the cannot be considered to involve an inventive step when the document is combined with one or more other such docu- | | | | | | |
| other means ments, such combination being obvious to a person skilled "P" document published prior to the international filing date but in the art. | | | | | | |
| | later than the priority date claimed & document member of the same patent family Date of the actual completion of the international search Date of mailing of the international search report | | | | | |
| <u> </u> | 5 November 1996 | - | · | | | |
| | | 0 6. 12. 9 | 8 | | | |
| Name and | mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 | Authorized officer | | | | |
| | NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+ 31-70) 340-3016 | Herygers, J | | | | |

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

It onal Application No
PCT/EP 96/03847

| Patent document cited in search report | Publication date | Patent family member(s) NONE | | Publication date |
|--|---------------------|---|--|--|
| DE-A-4024727 | 06-02-92 | | | |
| US-A-3854988 | 17-12-74 | NONE | | · |
| FR-A-2291251 | 11-06-76 | DE-A- DE-A- BE-A- CH-A- NL-A- SE-B- SE-A- | 2453658 2543035 835487 619256 7513262 425975 7512651 | 13-05-76 07-04-77 01-03-76 15-09-80 14-05-76 29-11-82 13-05-76 |

Form PCT/ISA/210 (patent family annex) (July 1992)

THIS PAGE BLANK (USPTO)